

Technical Data Sheet Evolve[®] PE Eclipse 140 - FL

Evolve[®] PE Eclipse 140 is a 4.13 oz. substrate designed for billboard applications. The material is specially formulated for high-speed UV printing. The product may be used for indoor or outdoor applications where a PVC free substrate is required. The material is available in 196" widths on 328' long rolls. Custom length rolls are available by special order.

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH		
Total Weight		140 gsm	4.13 oz./yd ²		
Base Fabric		PE			
Tensile Strength	ISO 13934-1: 2013 C.R.E. Strip Method	600 x 520 N/5cm	68.52 x 59.38 lb/in		
Tear Strength	ISO 13937-2:2000	110 x 110 N	24.73 x 24.73 lbf		
Elongation	ISO 13934-1: 2013 C.R.E. Strip Method	18.5 x 18%			

Applications

	Back-lit	Banner	Billboard	Block-out	Building Wrap	Display Systems	Truckside
Applications							

Ink Printability

Solvent	Eco	UV	Latex	Screen	Dye	Dye	,	Metric (m)	English (inches)
	Solvent			Printing	Transfer	Direct		Up to 5m	Up to 196"

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of the material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

www.ultrafleXX.com Updated: 06/2022

> Ultraflex Systems Inc. Headquarters 6333 Pelican Creek Circle, Riverview, FL 33578 P: (973)627-8608 Email: sales@Ultraflexx.com

Ultraflex Systems Inc. 1578 Sussex Turnpike, Bldg. 4 Randolph, NJ 07869 P: (973)627-8608 F: (973)627-8506 Email: sales@ultraflexx.com

Available Sizes

Ultraflex Europe Unit 15 Eltisley Business Park UK PE19 6TX

Abbotsley, Cambridgeshire Phone: (44)1767-677-100 Email: sales@ultraflexeurope.com